



GZY-72 UHF RFID Desktop Reader

1. EPC global UHF Class 1 Gen 2 / ISO 18000-6C standards
2. Working frequency 860-868MHZ, 902-928MHZ
3. Quick Excel import/export, boosts efficiency.
4. USB communication: simulated keyboard mode, driver-free.
5. Data communication for easy device interconnection.
6. Widely used in RFID: warehousing, fixed assets, personnel & document management.;



SPECIFICATIONS

RFID Performance :

Air interface	ISO-18000-6B、ISO-18000-6C (EPC G2)
Frequency range	865-868, 902-928MHZ (customized)
Antenna type	Near-field antenna
Polarization mode	Circular polarization
Communication interface	USB
Application software	Provide with DLL, support secondary development
Read distance	0~150mm
Write distance	0~100mm

Physical Performance :

Dimension	70(L)*13 (W)*11(H)mm
Fuselage material	ABS
Weight	150 g
Humidity	5% to 95%, non-condensing
Protection grade	IEC IP52
Operation temperature	-20 °C to +60 °C
Storage temperature	-40° C to 85° C
Heat dissipation	Air cooled

Note: Our company may optimize products in response to market changes, and any changes will be made without prior notice, please understand!



SHENZHEN INFO WISE TECHNOLOGY CO.,LTD.

Web : www.infowiserfid.com Email : sales@infowiserfid.com Tel : 0086-15361407827 office tel : 0086755-21005073

Add: 1101 & 1102, Building 5A, Huaqiang Creative Industry Park, Guangming Sub-district, Guangming District, Shenzhen City, Guangdong Province, P.R. China