



## GZY-T512 UHF RFID Antenna

1. IP67 protection, suitable for harsh outdoor environments.
2. EPC UHF Class 1 Gen 2/ISO 18000-6C standards.
3. Operating frequency band: 865-868/902-928MHz.
4. Supports N communication.
5. 12dbi Circular polarization minimizes polarization mismatch attenuation, enhancing signal reception.
6. Optimized design reduces EMI for stable operation in complex EM environments.



Warehouse



Asset Tracking



Personnel  
management



Library



Logistics

# SPECIFICATIONS


## RFID Performance:

RFID Frequency	865-868Mhz /920-928Mhz (Can be customized)
Gain	12dBi
Beam width	Hor: 70° Ver: 70°
Polarization	Circular
VSWR	≤1.4
F/B Ratio	≥20
Impedance	50Ω
Maximum power	50W
Lightning protection	DC Ground
Connector	N-female

## Physical Performance:

Working Temperature	-40°C to+70°C
Rated wind velocity	60m/s
Pole Diameter	Φ30-50mm
Colour	White
Material	ABS
Dimension	445*445*42mm

# DIMENSION



Note: Our company may optimize products in response to market changes, and any changes will be made without prior notice, please understand!



**SHENZHEN INFO WISE TECHNOLOGY CO.,LTD.**

Web: [www.infowiserfid.com](http://www.infowiserfid.com) Email: [sales@infowiserfid.com](mailto:sales@infowiserfid.com) Tel : 0086-15361407827 office tel : 0086755-21005073

Address: 1101 & 1102, Building 5A, Huaqiang Creative Industry Park, Guangming Sub-district, Guangming District, Shenzhen City, Guangdong Province, P.R. China